

u2 Filtered Water Tap



Installation Requirements

Mains fed water supply 1 x 240 V Electrical socket

Please ensure that there is sufficient under counter space available for the under counter unit. Additionally, the unit requires 150mm of clear space to the sides, front and rear and 100mm above.

The u2 Filtered Water Tap can be installed directly over a sink or as a stand-alone unit with a drip tray and drainage.

Under counter design

u2

Features

- Robust, solid build quality
- Simple to operate and maintain
- Chiller unit discretely installed under the counter
- Chilled, ambient and sparkling options available
- Two models 30 or 60 litres of chilled water per hour
- Twin or triple head tap
- Optional, stainless steel drip tray
- Mains fed

Dimensions:

Twin Head Tap

Height: 350mm Width: 220mm Depth: 250mm Dispense Height: 250mm **Triple Head Tap** Height: 470mm Width: 220mm Depth: 250mm Dispense Height: 285mm

30L Under Counter Unit

Height: 390mm Width: 230mm Depth: 370mm

Optional Drip Tray Width: 430mm Depth: 250mm

60L Under Counter Unit

Height: 485mm Width: 262mm Depth: 450mm



Mains fed water solutions for your workplace

Telephone 01934 631 666

National coverage, local care

www.glugglugglug.com